


MACHINE SPECIFICATION

DRUM DUMPER, DAPS



Machine name	DAPS	Manufacturer	Fluidor Equipment B.V.
Publication date	03-03-2026	Address	Ramgatseweg 25, 4941VN Raamsdonksveer, The Netherlands
Version	0.3	Telephone	+31(0)162 581 450

DESCRIPTION

The Drum Dumper (DAPS) is designed for an efficient emptying of 200 liter open top drums containing liquid products like fruit juice concentrates (up to 70° brix) with a maximum viscosity of up to 20.000 cP. Drums are placed on the roller conveyor section, at (optional) Drum Opening Station lid will be removed and liner(s) will be opened. The drums are transported to the Drum Dumper where drum is lifted and tipped pneumatically. The liner with product will fall into the collecting hopper and is stopped by a grid. The liner will empty itself partly. The operator brings the bottom part of the liner into the squeezer and the remaining product is squeezed out, the product flows into the product hopper and is discharged by a twin screw pump. After production CIP covers with rotating nozzle can be placed for integration into customer's CIP process.

DESIGN SPECIFICATION

- According actual CE-regulations
- Developed and built according quality system ISO 9001
- Clean design according actual EN1672-2 and HACCP-regulations
- Food contact materials according EC 1935/2004 and FDA
- Good Manufacturing Practice Regulation (EC) 2023/2006
- Components according Fluidor standard components list
- Machine prepared for integration into existing CIP-system (CIP covers included)
- Machine control by HMI
- Control cabinet IP55 / NEMA 12 (VX25, various sizes, AISI 304)
- Module for remote internet access
- Construction parts AISI304
- Product contact materials (hopper + piping parts) AISI 316
- Hygienic stainless steel hopper with dumping grid and integrated level detection
- Operator platform along right or left hand side of the machine
- Operator platform with stainless steel checker plate flooring
- Pneumatic loading and tilting device with pneumatic actuated clamping device, aluminum cylinders in a Clean design
- Electric driven bag squeezer with finger protection, hygienic design, consisting out of knurled AISI 316 lower roller and natural rubber upper roller, assembled in 2 AISI316-side plates with lifetime lubricated closed bearings, IP66 electric drive without cooling fan
- Product loss < 0,1%, with foot operated reverse drive for safe operation
- Frequency controlled twin screw product pump with seal flush and pressure relief valve set on 12 bar
- Pressure transmitter behind the pump
- Height roller conveyor system 700 mm
- CIP supply can optionally be supplied with a mix-proof valve.
- Machine is designed to be used 12 hours a day 5 days a week and 52 weeks a year with proper maintenance and an expected service life of 20 years



REQUIREMENTS

- Layout (dimensional, utility & requirements drawing) available upon request
- Earthquake area extra fixation needed (Anchors option)
- Machine is designed for indoor use in a medium hygiene wet area

TECHNICAL DATA

EU

USA

- | | | |
|--|------------------------------|---------------------------|
| · Total weight empty | : 2000 kg | 4410 lbs |
| · Total weight Full | : 2500 kg | 5510 lbs |
| · Product / CIP temp | : -20, +90 °C max 60 minutes | -4, 194 °F max 60 minutes |
| · Ambient temperature | : 5 - 25 °C | 41 - 77 °F |
| · Relative humidity | : 30 - 70% | |
| · Noise level | : < 85 dB(A) | |
| · IP value (control cabinets + drives) | : IP55 | |
| · Product hopper volume | : 500 L | 132 gal |
| · Pump particle size max | : 26 mm | 1.0 inch |
| · Adjustable machine support legs | : 80 -160 mm | 3.15 - 6.3 inch |
| · Dimensions h*w*d: | : 2400*1850*4250 mm | 94*73*167 inch |
| · Installed power | : 18 kW | 25 HP |

CAPACITY

- Depending on drum infeed & product: up to 60 drums per hour
- Pump capacity 4 - 12 m³ product per hour (18 - 52 gpm)
- Pump capacity 30 m³ CIP liquid per hour (132 gpm)
- Pump pressure max. 12 bar (174 psi)

PRODUCT INFORMATION

- Product type : Fruit juices and concentrates, liquid
- Product viscosity max : Dynamic viscosity 20.000 cP at a shear rate of 13 s⁻¹

CLEANING

- Cleaning depends on the product and company guidelines, the values below are guide values
- CIP cleaning after each production batch or before each production run after 12 hours of downtime
- Manual cleaning +- 20 min

CIP Time (sec)

CIP Step	Caustic	Caustic + Acid	Temperature (°C)	Concentration (%)
Pre Rinse	600	600	45	fresh water
Caustic (Organic soils)	1200	1200	75	0,5 - 2 % (Caustic soda)
Intermediate Rinse		600	20	fresh water
Acid (Inorganic soils)		600	65	0,5 - 1% (Acid)
Final Rinse	600	600	20	fresh water
Total CIP time (min)	40	60		

MAINTENANCE AND SERVICE

Remote support is available for this installation. Through a secure connection, we can analyze the installation, review data logging, provide remote maintenance support, and assist in resolving technical faults.

In addition, we offer tailored service agreements. This may include timely delivery of spare parts with instructions, or full maintenance based on defined service intervals.

Service options can be agreed with the customer during the project phase, helping to ensure reliable operation of the installation and reduced downtime.

RECOMMENDED MAINTENANCE INTERVALS

- General inspection : Every 1 week
- Emergency stop circuit testing : Every 3 months
- Minor maintenance : Every 6 months or 500 operating hours
- Major maintenance : Every 12 months or 1000 operating hours

BIN AND DRUM SPECIFICATION

- Dimensions drums:
- Max weight drum:

EU

Width: Ø480 to Ø630 mm
Height: 810 to 1000 mm
300 kg

USA

19.0" to 24.8" inches
31.8" to 39.4" inches
660 Lbs

MACHINE CONFIGURATIONS

- DAPS right
- DAPS left

POWER SUPPLY / CONTROLES

- 3 Phase 400V 50Hz 40 A+ neutral + earth, Siemens controls
- 3 Phase 480V 60Hz 35 A + earth, Allen-Bradley controls, UL prepared

COMMUNICATION

- PROFINET connections pre- installed at Siemens controls
- Ethernet/IP connections pre- installed at Allen Bradley controls


OPTIONS

- Water flow meter
- Magnetic trap in front of the pump
- Standing enclosure cabinets, IP66 / NEMA 4x (VX25, basic cabinet, AISI 304)
- External pump cooling for low product flow rate from 0 to 20 m³/h (standard range is from 8 to 20 m³/h)

PROCESS OPTIONS

The DAPS can be combined with the following Fluidor conveyor systems: Drum opening station, Drum weighing system, Drum conveyor load/unload, forklift protection, Drum sliding door, Drum washer full or empty drums, Drum crusher, Auto bag removal system ect.

PROJECT LAYOUT EXAMPLE



ANNEXED DOCUMENTS

- Machine Layout
- Machine P&ID
- Fluidor standard components

GENERAL INFORMATION

Website	: www.fluidor.com
Telephone	: +31 162 581450
Sales	: Mr. Jan Vermeulen
Telephone:	: +31 162 581457
Mobile	: +31 6 25009609
Email	: j.vermeulen@Fluidor.com
Spares	: Mr. Wing Ho Kwok
Telephone	: +31 162 581468
Email	: wh.kwok@fluidor.com
Service	: Service department
Telephone	: +31 162 581466
Email	: service@fluidor.com